

SIEMENS



New!

frame size
FSAA — up to
32% smaller

SINAMICS G120C

The perfect balance of performance, simplicity and cost-efficiency

usa.siemens.com/sinamics-g120c

The compact drive for countless applications

SINAMICS G120C — a new standard in its class

Compact in size and easy-to-operate, SINAMICS G120C provides world-class functionality in a highly-serviceable package for applications ranging from pumps, fans and compressors to mixers, extruders, conveyors and basic material handling machines.

SINAMICS offers numerous advantages:

- Common hardware and software
- Standard operator control and functionality
- Part of the Siemens Totally Integrated Automation (TIA) concept
- Common engineering approach with STARTER, Startdrive and SIZER tools
- Wide range of communication options including PROFINET and EtherNet/IP.

Decisive advantages for machine building

SINAMICS G120C was specifically designed for OEMs requiring a cost-effective, space-saving drive that is easy-to-operate and has a wide range of functionality. This drive unit is especially compact with a high power density and sets itself apart as a result of its fast installation and commissioning, user-friendly connections and simple commissioning tools. Safety functions (STO via terminal / with PROFIsafe) are already integrated — drive networking via standard fieldbus systems, as well as a memory card slot for cloning parameter sets, are also included.

UP TO
60%
ENERGY SAVING POTENTIAL

With four sizes, the SINAMICS G120C covers a power range from 0.55–18.5 kW (0.75–25 hp). The drive is equipped with vector control and comes with automatic flux reduction (ECO mode). Operator control and commissioning are quickly and easily achieved with a PC via USB or via the BOP-2 (Basic Operator Panel) or IOP (Intelligent Operator Panel). The G120C is an integral component of Totally Integrated Automation and has PROFINET, EtherNet/IP, PROFIBUS DP, USS/Modbus RTU, as well as CANopen communication interfaces. Commissioning and operation are quickly and easily achieved with a PC via USB, by the BOP-2 (Basic Operator Panel) or IOP (Intelligent Operator Panel).

SINAMICS — one family, one source, all applications.

The G120C is a part of the SINAMICS family of integrated drives, which offers the optimal drive for every application. As a result, these drives can be configured, parameterized, commissioned and operated in a similar fashion.



Low voltage		Medium voltage
SINAMICS G 0.12–2700 kW	SINAMICS S 0.12–4500 kW	SINAMICS GM/SM/GL 0.8–120 MW



Highlights at a glance

Mechanical design

- Compact
- Simple commissioning and maintenance
- Side-by-side mounting without derating
- Removable power terminals




Electronics

- Integrated braking chopper
- STO safety function
- IOP, BOP-2 and USB interface
- Optional interchangeable memory card (SD)
- Electrically isolated inputs

Communication

- PROFINET, EtherNet/IP, PROFIBUS DP, CANopen, USS/Modbus RTU
- Integral component of Totally Integrated Automation
- Supported profiles: PROFIenergy und PROFIsafe

SINAMICS G120C — advantages

G120C features		Your benefits
Small and rugged		
 <ul style="list-style-type: none"> ▪ FSAA needs up to 32% less space compared to FSA ▪ High power density, low envelope dimensions ▪ Several devices can be mounted side-by-side ▪ Operation up to an ambient temperature of 60° C 	<ul style="list-style-type: none"> ▪ Simple installation in the smallest space ▪ Low space requirement ▪ Long service life, high reliability ▪ Can be used in small control cabinets, close to the machine 	
User-friendly		
 <ul style="list-style-type: none"> ▪ Optimized parameter set ▪ Optimized commissioning ▪ Getting Started document ▪ BOP-2 and IOP operator panels can be used ▪ Integrated USB port ▪ Identical options 	<ul style="list-style-type: none"> ▪ Simple and fast software parameterization ▪ Simple operability during commissioning and in operation ▪ Minimized training costs ▪ Service-friendly ▪ Options for SINAMICS FSA and MICROMASTER MM4 can also be used for the new frame size FSAA 	
Installation and maintenance		
 <ul style="list-style-type: none"> ▪ Removable power terminals ▪ Cloning function using BOP-2, IOP or SD card ▪ G120C integrated into Siemens TIA ▪ FSAA is fully compatible with the other three frame sizes 	<ul style="list-style-type: none"> ▪ Fast mechanical installation ▪ Intuitive series commissioning ▪ Integration in the automation environment ▪ When a MICROMASTER MM4 is being replaced, new dimensioning is not required as the drilling template is identical to SINAMICS FSA 	
Leading technology functions		
 <ul style="list-style-type: none"> ▪ Energy-efficient, encoderless vector control ▪ Automatic flux reduction with V/f ECO ▪ Integrated energy calculator ▪ Safety Integrated (STO) ▪ Supported profiles: PROFIsafe, PROFIenergy 	<ul style="list-style-type: none"> ▪ High control quality ▪ Energy-efficient motor control ▪ Energy-saving can be measured ▪ Standard integrated safety functions without additional costs; no external components are required as a result of the certified Safe Torque Off (STO) safety function 	
State-of-the-art communication		
 <p>The following communication versions are available:</p> <ul style="list-style-type: none"> ▪ PROFINET, EtherNet/IP ▪ PROFIBUS DP ▪ CANopen ▪ USS/Modbus RTU 	<ul style="list-style-type: none"> ▪ Uses all of the common bus systems ▪ Flexible use ▪ Reliable communication ▪ Can be simply plugged in ▪ Uninterruptible, due to the optional 24V power supply 	

Selection and ordering information



Rated data				Order Number	Frame size	Dimensions		
P_{LO^1} kW	P_{LO^1} Hp	$I_{LO^1_out}$ A	$I_{HO^2_out}$ A			W	H	D ³
3-phase supply voltage 380–480V								
0.55	0.75	1.7	1.3	6SL3210-1KE11-8	2	73 mm 2.87 in.	173 mm 6.81 in.	155 mm 6.10 in. (PROFINET, EtherNet/IP: + 22.4 mm)
0.75	1.0	2.2	1.7	6SL3210-1KE12-3	2			
1.1	1.5	3.1	2.2	6SL3210-1KE13-2	2			
1.5	2.0	4.1	3.1	6SL3210-1KE14-3	2			
2.2	3.0	5.6	4.1	6SL3210-1KE15-8	2			
3	4.0	7.3	5.6	6SL3210-1KE17-5	1	196 mm 7.72 in.	203 mm 8.87 in.	(PROFINET, EtherNet/IP: + 22.4 mm)
4	5.0	8.8	7.3	6SL3210-1KE18-8	1			
5.5	7.5	12.5	8.8	6SL3210-1KE21-3	1	100 mm 3.94 in.	295 mm 11.61 in.	(PROFINET, EtherNet/IP: + 22.4 mm)
7.5	10.0	16.5	12.5	6SL3210-1KE21-7	1			
11	15.0	25.0	16.5	6SL3210-1KE22-6	1	140 mm 5.51 in.	295 mm 11.61 in.	(PROFINET, EtherNet/IP: + 22.4 mm)
15	20.0	31.0	25.0	6SL3210-1KE23-2	1			
18.5	25.0	37.0	31.0	6SL3210-1KE23-8	1			
EMC filter								
Integrated EMC Class A/C2 filter ⁴					A			
Unfiltered version					U			
Integrated communication interface								
RS485 with USS / Modbus RTU					B			
SUB-D with PROFIBUS DP					P			
PROFINET, EtherNet/IP					F			

¹ LO = Low Overload
² HO = High Overload
³ Frame size FSA- FSC with PROFINET, EtherNet / IP depth: additional, 22.4mm
⁴ For detailed information on maintaining interference classes, refer to the product documentation
⁵ The continuous output current is not reduced when using the overload capability

Technical data	
Voltage / frequency	3-phase 380–480V –20% +10% with 50 / 60 Hz +/–5%
Power range	0.55–18.5 kW / 0.75–25 hp
Overload power	For I_{LO_out} (LO ¹): 150% for 3 sec. plus 110% for 57 sec. within a 300 sec. load cycle For I_{HO_out} (HO ²): 200% for 3 sec. plus 150% for 57 sec. within a 300 sec. load cycle ⁵
Degree of protection	IP20 / UL open type
Ambient temperature	-10 to 40° C without derating / up to 60° C with derating
EMV drives with Class A filter	<ul style="list-style-type: none"> Device fulfills the requirements according to EN 61800-3 Category C3 (industrial low-voltage line supplies) Device complies with the limit values of cable-conducted and radiated interference voltages according to EN 61800-3 Category C2 (public low-voltage grid)
Motor cable lengths	50 m shielded / 100 m unshielded
Signal inputs / outputs	6 DI / 2 DO / 1 AI / 1 AO
Safety technology	SIL 2 acc. EN 61508, PL d acc. EN ISO 13849, class 3 acc. EN 60204, Safe Torque Off (STO)
Control modes	Vector, V/f, V/f ECO
Energy functions	Energy-saving calculator, energy consumption calculator, automatic flux reduction
Function	Fixed velocity / speed setpoint, 2/3 wire control, PID controller, motor holding brake control
Braking	Integrated braking chopper

Options		
Braking resistor		
FSA	0.55–1.5 kW	6SL3201-0BE14-3AA0
FSAA/FSA	2.2–4 kW	6SL3201-0BE21-0AA0
FSB	5.5–7.5 kW	6SL3201-0BE21-8AA0
FSC	11–18.5 kW	6SL3201-0BE23-8AA0
Input reactor		
FSA	0.55–1.1 kW	6SL3203-0CE13-2AA0
FSAA/FSA	1.5–4 kW	6SL3203-0CE21-0AA0
FSB	5.5–7.5 kW	6SL3203-0CE21-8AA0
FSC	11–18.5 kW	6SL3203-0CE23-8AA0
Output reactor		
FSA	0.55–2.2 kW	6SL3202-0AE16-1CA0
FSA	3–4 kW	6SL3202-0AE18-8CA0
FSB	5.5–7.5 kW	6SL3202-0AE21-8CA0
FSC	11–18.5 kW	6SL3202-0AE23-8CA0
Operator panels		
BOP-2	Basic Operator Panel	6SL3255-0AA00-4CA1
IOP	Intelligent Operator Panel	6SL3255-0AA00-4JA1

Siemens Industry, Inc.
 5300 Triangle Parkway, Suite 100
 Norcross, GA 30092
 1-770-871-3800

Order No. DRBR-G120C-1215
 Printed in USA
 © 2014 Siemens Industry, Inc.

The information provided in this brochure contains only general descriptions or performance features, which do not always apply in the manner described in concrete application situations or may change as the products undergo further development. Performance features are valid only if they are formally agreed upon when the contract is closed. Siemens is a registered trademark of Siemens AG. Product names mentioned may be trademarks or registered trademarks of their respective companies. Specifications are subject to change without notice.